

CEN-PE-CO AUTOMATIC TRANSMISSION FLUID

A heavy duty automatic transmission fluid exceeding the requirements of both DEXRON® II and Ford MERCON® (pre-1992 version) specifications.

OUTSTANDING FEATURES AND BENEFITS:

100% pure paraffin base for
exceptional heat resistance
Compatible with all seal materials

Reduces wear
Excellent rust and oxidation protection
Extends transmission life

EXCEEDS SPECIFICATIONS:

DEXRON® II
Ford MERCON® II (pre-1992)
Ford M2C138-CJ, M2C166-H
General Motors 6137
Allison C-3, C-4

Caterpillar TO-2
Sunstrand Hydraulic Pump
Denison Hydraulic
Sperry Vickers Hydraulic
AGCO 411

CONTAINERS:

55 Gallon Drum
35 Gallon Drum
20 Gallon Drum

5 Gallon Pail
1 quart can (24 per case)

TYPICAL CHARACTERISTICS:

Viscosity

SUS @ 210° F. 50

SUS @ 100° F. 172

cSt @ 100° C. 7.3

cSt @ 40° C. 37

Viscosity Index 150

Flash Point 380° F.

Pour Point -40° F.

Seal Compatibility (GM & Ford Methods) Pass


Color Red

Central Petroleum Company

11810 Madison Ave.
Cleveland, OH 44107-0597

201 East Lincoln Street
Walcott, IA 52773-0116

800-553-1891 FAX 563-284-5124



CEN-PE-CO AUTOMATIC TRANSMISSION FLUID

LIMITATIONS:

Cen-Pe-Co Automatic Transmission Fluid is not recommended for:

- Transmission calling for DEXRON® III
- Transmissions calling for MERCON V
- Post-1992 transmissions calling for MERCON®
- Applications at temperatures below -40° F.

Cen-Pe-Co Synthetic Blend ATF exceeds these specifications and is recommended in these applications.

Central Petroleum Company believes that most fluids designed to meet the cold temperature flow requirements of these newer specifications lack the film strength needed for heavy-duty applications. Cen-Pe-Co Automatic Transmission Fluid is superior for any application calling for DEXRON® II or pre-1992 MERCON®.