

CEN-PE-CO ALL PURPOSE 2-CYCLE OIL

Cen-Pe-Co All Purpose 2-Cycle Oil is designed for the most severe, high-temperature service. It can be used in most air cooled or water cooled 2-cycle gasoline engines, whether injected or pre-mixed at the manufacturer's recommended rate.

OUTSTANDING FEATURES AND BENEFITS:

- Provides superior varnish and deposit control
- Prolongs filter life
- Ashless to inhibit pre-ignition
- Assures longer, trouble-free engine life
- Tints fuel red for easy identification of pre-mixed fuel

APPLICATIONS:

Power Boats	Chain Saws
Snowmobiles	Lawn Equipment
Motorcycles	Other 2-Cycle Engines

RECOMMENDED WHERE THE FOLLOWING FLUIDS ARE SPECIFIED:

NMMA TC-W3[®], TC-W II[®], TC-W[®], BIA
API TD, TC, TB, TA

CONTAINERS:

55 gallon drum	5 gallon pail
35 gallon drum	1 Quart Measuring Bottle (12 per case)
20 gallon drum	

TYPICAL CHARACTERISTICS:

Viscosity	
cSt @ 100° C	7.2
SUS @ 210° F	48
Sulfated Ash	None
Pour Point	-22° F
Density	7.4 Pounds Per Gallon
Color	Red

TC-W3, TC-W II, and TC-W are registered trade names of the National Marine Manufacturers Association.

Central Petroleum Company

11810 Madison Ave.
Cleveland, OH 44107-0597

201 East Lincoln Street
Walcott, IA 52773-0116

800-553-1891 FAX 563-284-5124

