

CEN-PE-CO CVT HYDRAULIC OIL

Cen-Pe-Co CVT Hydraulic Oil is a superior tractor hydraulic oil designed to excel in almost every make and model of farm equipment where the hydraulics, drive gears, and wet brakes are within the same system. It is particularly resistant to viscosity loss under the crushing forces of modern CVT tractors. This multi-functional fluid is also the correct lubricant for many hydrostatic systems, straight hydraulic systems, and industrial power transmissions.

Cen-Pe-Co CVT Hydraulic Oil is a more shear stable version of Cen-Pe-Co Multi-Purpose Hydraulic & Wet Brake Oil, and the two fluids are completely compatible.

OUTSTANDING FEATURES AND BENEFITS:

- Reduces wear of gears, pumps, wet brakes, clutches, and bearings by up to 94%
- Maintains its viscosity, even in CVT tractors, for superior temperature control and efficiency
- 100% Pure Paraffin Base oil resists breakdown for higher heat resistance and longer lasting protection
- Superior low temperature power steering, hydraulic, and hydrostatic response
- Reduces brake chatter
- In many cases, lowers operating temperatures

EXCEEDS SPECIFICATIONS:

Recommended where the following fluids are specified:

AGCO 821XL

Allis Chalmers Gear, Hydraulic and Wet Brake Oil, Power Fluid 821

Allison C-3 and C-4 Transmission Fluid

API GL4

Case Powerguard PTF Fluid, TCH, TFD I-II, JIC 145, JIC 185

Case IH Hy-Tran Ultraction®, Hy-Tran® Ultra, Nexlore® MAT 3540, MAT 3525, MAT 3505, B-6, MS-1204, MS-1205, MS-1206, MS-1207, MS-1209, MS-1230, MS-1317

Case New Holland MAT 3540, MAT 3525, MAT 3509, MAT 3505, ESN M2C86B

Caterpillar MTO, TO-2

Class/Renault transmissions

David Brown THF-1257 Fluid

Deutz Hydraulic Transmission Fluid

Deutz-Allis AC Power Fluid 821XL

Deutz-Fahr

Fiat-Hesston

Central Petroleum Company

11810 Madison Ave.
Cleveland, OH 44107-0597

201 East Lincoln Street
Walcott, IA 52773-0116

800-553-1891 FAX 563-284-5124



CEN-PE-CO CVT HYDRAULIC OIL

Ford M2C 48B-C3, M2C 53A-B, M2C 86A-C, M-2C 134A-D

Ford New Holland FNHA-2-C-200.00, FNHA-2-C-201.00

International Harvester Hy-Tran® Fluid B-6

JCMAS (Japanese Constructors Mechanization Association) HK P-041, P-42

John Deere HyGard®, Quatrol®, 303, J20A, J20C

Komatsu, Komatsu Dresser B06-0002

Kubota Hydraulic Transmission Fluid, UDT, Super UDT

Landini

Massey-Ferguson Permatran® III, M1127A-B, M1129A, M1110, M1135, M1141, M1143, M1145

Minneapolis-Moline Universal Hydraulic Transmission Fluid

New Holland MAT 3540, MAT 3525, MAT 3509, MAT 3505, NH 646H, NH401B-C, M2C41A-B, M2C48B-C, M2C53A-B, M2C86A-B-C, M2C134A-B-C-D

Oliver Universal Hydraulic Transmission Fluid, Type 55 Fluid

Same transmissions

Sperry New Holland 287530

Steiger Hydraulic-Wet Brake Oil

Sunstrand HMS 103

Versatile Gear-Hydraulic-Wet Brake Oil

Volvo WB101, VCE 1273.03

White New Idea Q-186, Q-1705, Q-1722, Q-1766, Q-1802, Q-1826

ZF TE-ML-03E, 05F, 06K, 17E

Hy-Tran and Nexlore are trademarks of Case New Holland. HyGard and Quatrol are trademarks of John Deere. Permatran is a trademark of AGCO.

CONTAINERS:

55 Gallon Drum

35 Gallon Drum

20 Gallon Drum

5 Gallon Pail

2 Gallon Jugs (4 per case)

TYPICAL CHARACTERISTICS:

Viscosity

cSt @ 100° C.

9.8

cSt @ 40° C.

63

Viscosity Index

140

Pour Point

-38° F.

Cold Crank Simulator @ -20° C.

4800 cP

Zinc

.15%