

CEN-PE-CO DOUBLE DUTY PRESSURE LUBE

A multi-purpose grease that is unsurpassed in load-bearing capabilities, sustained high temperature applications, and durability.

OUTSTANDING FEATURES AND BENEFITS:

- Outperforms most melt-proof greases at sustained elevated temperatures (350°F)
- High heat resistance (500°F)
- Tremendous mechanical stability - does not thin out with use
- Extremely adhesive
- Superior staying power
- Withstands high shock loads and pressures (65 lb Timken)
- Excellent water resistance Prevents rust
- Good cold temperature pumpability (0°F)
- Seals against water and dust
- Reduces wear

PRIMARY USES:

- Wheel bearings, including those with disc brakes.
- Extreme pressure applications in construction equipment.
- Low to high speed applications.
- Ball and roller anti-friction bearings, and sleeve bearings.
- Applications that squeeze out ordinary greases.
- Applications at temperatures that cause ordinary greases to run.
- A wide variety of farm, construction, automotive, and industrial applications.

CONTAINERS:

- 120 pound keg
- 50 pound pail
- 14 1/2 ounce cartridge (30 per case)

Central Petroleum Company

11810 Madison Ave.
Cleveland, OH 44107-0597

201 East Lincoln Street
Walcott, IA 52773-0116

800-553-1891 FAX 563-284-5124



CEN-PE-CO DOUBLE DUTY GREASE

TYPICAL CHARACTERISTICS:

Penetration, worked	265-295
Penetration, worked 100,000	± 10% from orig.
Thickener, type	Lithium 12 Hydroxy Complex
Color	Green
Texture	Tacky, Med. Fiber
Dropping Point °F., D-2265	>500
Timken #OK Load	65 lbs.
Rust D-1743	1, 1, 1
Four Ball, mm	.37
Weld load, kg	315
Load wear index	45