

CEN-PE-CO HYDROSTATIC FLUID

A heavy duty hydrostatic fluid, hydraulic oil, and Type F automatic transmission fluid. It is formulated with 100% pure paraffin base oil fortified with high performance additives.

PROVIDES SUPERIOR:

Heat Resistance	Seal Compatibility
Anti-Wear Protection	Lubricant and Equipment Life
Corrosion Resistance	

APPLICATIONS:

Hydrostatic drives
Agricultural and industrial transmissions and clutches
Ford power steering pumps
Pre-1977 Ford light truck and passenger car automatic transmissions
Some 1977-1980 Ford light truck and passenger car automatic transmissions

SPECIFICATIONS:

John Deere J21A
Ford M2C33-G, M2C33-F
Ford Type F

CONTAINERS:

55 gallon drum	20 gallon drum
35 gallon drum	5 gallon pail

TYPICAL CHARACTERISTICS:

Viscosity	
cSt @ 40° C	42
cSt @ 100° C	7.6
SUS @ 100° F	195
SUS @ 210° F	51
Viscosity Index	140
Flash Point	390° F
Pour Point	-40° F
Seal Compatibility (Ford Procedure)	Pass
Color	Red

Central Petroleum Company

11810 Madison Ave.
Cleveland, OH 44107-0597

201 East Lincoln Street
Walcott, IA 52773-0116

800-553-1891 FAX 563-284-5124

