

CEN-PE-CO J-20 C OIL

A superior hydraulic and wet brake oil for use in John Deere farm and industrial equipment where the hydraulics and drive gears are part of the same system.

OUTSTANDING FEATURES AND BENEFITS:

Reduces wear of gears, pumps, wet brakes, clutches, and bearings by up to 94% 100% Pure Paraffin Base oil resists breakdown for higher heat resistance and longer lasting protection

Superior low temperature power steering, hydraulic, and hydrostatic response Reduces brake chatter

In many cases, lowers operating temperatures

EXCEEDS SPECIFICATIONS:

Recommended where the following fluids are specified:

John Deere Quatrol® John Deere Hy-Gard® John Deere J-20 C John Deere J-30 A John Deere 303

CONTAINERS:

55 Gallon Drum 5 Gallon Pail 35 Gallon Drum 20 Gallon Drum

TYPICAL CHARACTERISTICS:

Viscosity	
SAE	
SUS @ 210° F.	57
SUS @ 100° F.	283
cSt @ 100° C.	9.5
Viscosity Index	140
Pour Point	-35° F.
Cold Crank Simulator @ -20° C.	2500 cPs
Shear Stability (% of Loss)	6
Zinc	.13%

Hy-Gard and Quatrol are registered trademarks of Deere and Company.

Central Petroleum Company

11810 Madison Ave. Cleveland, OH 44107-0597 201 East Lincoln Street Walcott, IA 52773-0116

800-553-1891 FAX 563-284-5124

