

# **cen-pe-co** **PRODUCT DATA**

## **CEN-PE-CO MEGA MOLY** THE GREASE WITH GUTS

A high solids Moly grease designed especially for construction equipment and other heavily loaded, extreme pressure applications.

### **OUTSTANDING FEATURES AND BENEFITS:**

- High Moly content (5% solids)
  - Eliminates hot spots
  - Delaminates to reduce wear
  - Lubricates at pressures and temperatures that destroy ordinary grease film
- Eliminates squeaking pins and bushings
- High heat resistance (>500° dropping point)
- Great mechanical stability—does not break down when worked
- Excellent water resistance
- Extremely adhesive—great staying power
- Cold weather pumpability to 0°F.

### **PRIMARY USES:**

- Bucket pins and pivot points on construction equipment
- Universal joints on heavy-duty trucks and heavy equipment
- King pins, 5th wheels, ball joints, chassis points
- Practically any heavy-duty, sliding application

### **CONTAINERS:**

- 120 pound keg
- 50 pound pail
- 14 1/2 ounce cartridge (30 per case)

### **Central Petroleum Company**

11810 Madison Ave.  
Cleveland, OH 44107-0597

201 East Lincoln Street  
Walcott, IA 52773-0116

800-553-1891 FAX 563-284-5124



## CEN-PE-CO MEGA MOLY

### TYPICAL CHARACTERISTICS:

NLGI#	2
Penetration, worked 60 strokes (ASTM D217)	280
Penetration, worked 100,000 strokes (ASTM D217)	<6% change
Dropping Point (ASTM D2265)	525°F.
Molybdenum Disulfide Solids	5%
Timken OK Load (ASTM D2509)	60 lbs.
4-Ball Weld (ASTM D2596)	>800 kg
Water Washout (ASTM D1264)	4%
Water Spray Off (ASTM D4049)	15%
Rust Prevention	Excellent
Thickener	Lithium Complex
Specific Gravity	0.93
Color	Moly Gray
Texture	Smooth, Tacky