

CEN-PE-CO SYNTHETIC OIL & CEN-PE-CO PV SYNTHETIC BLEND OIL

Cen-Pe-Co Synthetic Oil and Cen-Pe-Co PV Synthetic Blend Oils are designed specifically for turbocharged and naturally aspirated gasoline engines in Personal Vehicles—cars, pickup trucks, and SUVs. The only difference in their formulation is Cen-Pe-Co Synthetic Oil is fully synthetic and PV Synthetic Blend uses a blend of synthetic base oil and pure paraffin base oil.

These oils are particularly well suited for TGDI (turbocharged gasoline direct injection) engines, but are equally suited for gasoline powered passenger vehicles manufactured since 2004.

OUTSTANDING FEATURES AND BENEFITS:

- Formulated to avoid Low Speed Pre-Ignition (LSPI) in TGDI engines
- Extra dispersants for improved cleanliness
- Superior anti-wear performance to prevent timing chain elongation
- Superior oxidation (breakdown) resistance for longer turbo life
- Reduced oil consumption over the life of the engine
- Easy cold weather starting
- Outstanding shear stability (resistance to viscosity breakdown)
- Longer drain protection

EXCEEDS SPECIFICATIONS:

API SP, SN+, SN, SM
Although it was not licensed by GM, Cen-Pe-Co Synthetic Oil exceeds the wear requirements of GM's dexos™ 1 Gen 2

VISCOSITY GRADES:

PV Synthetic Blend Oil	Synthetic Oil
SAE 5W-30	SAE 0W-20
SAE 10W-30	SAE 5W-20
	SAE 5W-30

CONTAINERS:

55 Gallon Drum	2 Gallon Jug (4 per case)
35 Gallon Drum	1 Gallon Bottle (6 per case)
5 Gallon Pail	1 Quart Bottle (12 per case)

Central Petroleum Company

11810 Madison Ave.
Cleveland, OH 44107-0597

201 East Lincoln Street
Walcott, IA 52773-0116

800-553-1891 FAX 563-284-5124



CEN-PE-CO SYNTHETIC OIL & CEN-PE-CO PV SYNTHETIC BLEND OIL

	Synthetic			PV Synthetic Blend	
Viscosity					
SAE	0W-20	5W-20	5W-30	5W-30	10W-30
cSt 40 C	50	47	65	62	66
cSt 100 C	9.3	8.4	10.4	10.6	10.5
Viscosity Index	171	156	148	162	147
Zinc (PPM)	830	830	830	830	830
TBN	9.2	9.2	9.2	9.2	9.2
Sulfated Ash %	0.9	0.9	0.9	0.9	0.9
Specific Gravity	.86	.86	.86	.85	.85