

## **CEN-PE-CO WINTER SYNTHO LUBE**

A winter version of Cen-Pe-Co Syntho Lube providing excellent flow, pumpability, and lubrication at cold temperatures.

### **OUTSTANDING FEATURES AND BENEFITS**

Excellent cold weather pumpability – pumps at -10° F. like regular Syntho Lube pumps at 70° F.  
Superior lubrication and less drag at subzero temperatures.  
High heat resistance (530° F.)  
Carries extreme pressure loads (60 lb. Timken).  
Excellent mechanical stability – does not thin out with use.  
Excellent water resistance.

### **LIMITATIONS**

Not recommended for rigorous applications at high ambient temperatures where NLGI #2 greases are required.

### **TYPICAL CHARACTERISTICS:**

Penetration (Worked 60 Strokes)	ASTM D217	322
Penetration (Worked 100,000 Strokes)	ASTM D217	< 5% change
NLGI#		1
Dropping Point	ASTM D2265	530° F.
Timken OK Load	ASTM D2509	60 lb.
4-Ball Weld Point	ASTM D2596	400 Kgf
Wheel Bearing Life Test (80 hours is the minimum pass)	ASTM D3527	120 hours
Thickener		Lithium Complex
Color		Red
Texture		Smooth, Tacky

### **Central Petroleum Company**

11810 Madison Ave.  
Cleveland, OH 44107-0597

201 East Lincoln Street  
Walcott, IA 52773-0116

800-553-1891 FAX 563-284-5124

