

CEN-PE-CO AQUA LUBE

A heavy-duty, multi-purpose grease with phenomenal adhesiveness and stability in the presence of water.

OUTSTANDING FEATURES AND BENEFITS:

- Exceptional water resistance
- Extremely adhesive, even in the presence of water
- Excellent mechanical stability, even in the presence of water
- Superior staying power, even in wet environments
- Prevents rust
- Good cold temperature pumpability (0°F.)
- Seals against water, dust, and chemicals

PRIMARY USES:

- Wheel bearings, ball and roller bearings, and sleeve bearings
- Paper machines
- Sewage treatment plants
- Steel mills
- Underwater dredges
- Boat trailer wheel bearings
- Irrigation equipment
- Fifth wheels
- Fertilizer equipment
- A wide variety of farm, construction, automotive, and industrial applications
- Wet environments that cause ordinary grease to fail

CONTAINERS:

- 120 pound keg
- 50 pound pail
- 14 1/2 ounce cartridge (30 per case)

Central Petroleum Company

11810 Madison Ave.
Cleveland, OH 44107-0597

201 East Lincoln Street
Walcott, IA 52773-0116

800-553-1891 FAX 563-284-5124



CEN-PE-CO AQUA LUBE

TYPICAL CHARACTERISTICS:

NLGI#	2
Water Spray Off (ASTM D4049)	18% loss
Water Washout @ 175°F. (ASTM D1264)	2.4% loss
Penetration, worked 60 strokes (ASTM D217)	280
Dropping Point (ASTM D2265)	390°F.
Timken OK Load (ASTM D2509)	40 lbs.
4-Ball Weld (ASTM D2596)	315 kg
4-Ball Load Wear Index (ASTM D2596)	54.4 kg
Roll Stability (ASTM D1831) (Wet)	+15%
Mobility (US Steel Test)	2 gm/min @ 0°F.
Rust Prevention	Excellent
Thickener	Lithium
Color	Black
Texture	Fibrous, Tacky