

cen-pe-co **PRODUCT DATA**

CEN-PE-CO SEVERE SERVICE OIL **Straight Grades (SAE 10W, 20W, 30)**

Cen-Pe-Co Severe Service Oil is especially formulated for gasoline engines operated under severe loads, severe temperatures, high RPM, or other severe service conditions. It contains additional zinc anti-wear additive (ZDDP), that is missing from modern passenger car oils, to protect flat tappet cams.

OUTSTANDING FEATURES AND BENEFITS:

Formulated with 100% Pure Paraffin Base Oils
Superior wear performance
Extra zinc (ZDDP) anti-wear additive
Additional oxidation inhibitors for greater resistance to oil breakdown
More rust inhibitors for storage protection

EXCEEDS SPECIFICATIONS:

API SL, SJ, SH, SG, SF, CD

CONTAINERS:

55 Gallon Drum	5 Gallon Pail
35 Gallon Drum	2 Gallon Jug (4 per case)
20 Gallon Drum	1 Gallon Bottle (6 per case)

TYPICAL CHARACTERISTICS:

Viscosity			
SAE	<u>10W</u>	<u>20</u>	<u>30</u>
cSt @ 100° C.	7.0	8.6	12.3
cSt @ 40° C.	49	67	112
Viscosity Index	99	99	100
Zinc Content (PPM)	>1200	>1200	>1200

Central Petroleum Company

11810 Madison Ave.
Cleveland, OH 44107-0597

201 East Lincoln Street
Walcott, IA 52773-0116

800-553-1891 FAX 563-284-5124

