

MATERIAL SAFETY DATA SHEET

**Section 1: PRODUCT AND COMPANY IDENTIFICATION**

Central Petroleum Company  
201 East Lincoln Street  
Walcott, IA 52773-0116

Phone Number: 563-284-6221  
Monday-Friday, 8:00 a.m. - 3:45 p.m. CST  
Fax Number: 563-284-5124  
Emergency:  
CHEMTREC 1-800-424-9300

Product Name: Columbia Acro-Plex House White  
Common Name: Acrylic Water Base Paint

Issued Date: 07/24/08  
Supersedes Date: 01/92

**Section 2: HAZARDS IDENTIFICATION**

EMERGENCY OVERVIEW

Appearance/Odor: White liquid with a paint odor.

Potential Health Effects: See Section 11 for more information

Likely Routes of Exposure: Eye and skin contact

- Eye: May cause moderate eye irritation including pain, tearing, redness, and swelling.
- Skin: May cause moderate skin irritation including redness, swelling, and rash. Prolonged contact may cause skin damage, defatting, and dermatitis. Absorption through the skin may cause symptoms of exposure as described for inhalation and ingestion.
- Ingestion: Expected to be moderately toxic. May cause gastrointestinal irritation, including sore throat, abdominal pain, nausea, vomiting, and diarrhea. Ingestion may cause central nervous system depression. May cause kidney damage, lumbar pain, oliguria, or uremia. Extreme cases of intoxication may cause unconsciousness and death.
- Inhalation: May cause irritation to the nose, throat, respiratory tract, and other mucous membranes. Symptoms of respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath, and reduced lung function. Exposure to high concentrations of vapor may cause central nervous system depression. Symptoms of central nervous system depression include headache, dizziness, and nausea. Intentional misuse by deliberate concentration and inhalation of this material may be harmful or fatal.

This material may contain components classified as nuisance particulates, which may be present at hazardous levels only during sanding or abrading of the dried film.

Medical Conditions Aggravated By Exposure:

May cause more significant irritation in people with pre-existing skin, eye, and respiratory conditions. Impaired central nervous system functions from pre-existing disorders may be aggravated by exposure to this product.

This product contains no carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

MATERIAL SAFETY DATA SHEET

**Section 3: COMPOSITION/INFORMATION ON INGREDIENTS**

<u>Component</u>	<u>CAS#</u>	<u>% by Wt.</u>
Titanium Dioxide	13463-67-7	10-15
Kaolin	1332-58-7	5-10
Ethylene Glycol	107-21-1	1-5
Propylene Glycol	57-55-6	1-5

**Section 4: FIRST AID MEASURES**

Eye Contact:	Flush eyes with water for at least 15 minutes. Seek medical attention if irritation persists.
Skin Contact:	Remove contaminated clothing and wash before reuse. Remove excess from skin and wash with soap and water. Seek medical attention if symptoms persist.
Ingestion:	If victim is awake and alert, administer two glasses of water. Induce vomiting by giving two tablespoons of ipecac or by touching a finger to the back of the victim's throat. Keep the victim's head below the hips to prevent aspiration into the lungs. Seek immediate medical attention.
Inhalation:	Move to fresh air. Provide oxygen if breathing is difficult. Provide artificial respiration if the victim is not breathing. Seek medical attention immediately.

Note to Physicians:

Ethylene glycol may cause kidney damage and metabolic acidosis. Ethanol is antidotal, and its early administration may block the formation of nephrotoxic metabolites of ethylene glycol in the liver. Ethanol should be given intravenously, as a solution in sodium bicarbonate, at a rate of about 10-mL ethanol per hour. A desired therapeutic level of ethanol in blood is 100 mg/dl. Hemodialysis may be required. Pulmonary edema with hypoxemia has been described in a number of patients following poisoning with ethylene glycol. The mechanism of production has not been elucidated, but it appears to be noncardiogenic in origin in several cases. Respiratory support with mechanical ventilation and positive end-expiratory pressure may be required.

**Section 5: FIRE FIGHTING MEASURES**

Suitable Extinguishing Media:  
Not applicable.

Protection of Firefighters:  
Firefighters should wear self-contained breathing apparatus and full fire-fighting turnout gear.

Unusual Fire and Explosion Hazards:  
Not applicable.

**Section 6: ACCIDENTAL RELEASE MEASURES**

Personal Precautions:  
Use personal protection recommended in Section 8.

MATERIAL SAFETY DATA SHEET

Environmental Precautions:

Prevent entry into sewers and waterways.

Methods for Containment and Cleanup:

Recover material with vacuum trucks or pump to storage/salvage vessels. Absorb residue with material such as clay or sand. Place in non-leaking containers for proper disposal. Flush area with water to remove trace residue.

**Section 7: HANDLING AND STORAGE**

Handling:

Keep containers closed when not in use. Wash thoroughly after handling. Empty containers may contain product residue, which may exhibit the hazards of the product.

Storage:

Store in closed, labeled containers.

**Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

Exposure Guidelines:

Titanium Dioxide

OSHA TWA: 15 Mg/M<sup>3</sup>

ACGIH TWA: 10 Mg/M<sup>3</sup> (Total Dust)

Kaolin

ACGIH TWA: 10 Mg/M<sup>3</sup> (Total Dust)

Ethylene Glycol

ACGIH TWA: 50 ppm (Ceiling)

Nuisance Dusts

ACGIH TLV: 10 Mg/M<sup>3</sup> (Total Dust)

OSHA PEL: 15 Mg/M<sup>3</sup> (Total Dust)

Engineering Controls:

Sufficient ventilation, in volume and pattern, should be provided to keep the vapor concentration below applicable OSHA requirements.

Eye/Face Protection:

Wear safety glasses, goggles, or a splash shield to prevent eye contact. Do not wear contact lenses.

Skin Protection:

Wear protective gloves and other protective clothing as needed to prevent contact with skin and clothing.

Respiratory Protection:

If exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted NIOSH approved respirator.

General Hygiene Considerations:

Wash hands before eating, drinking, or using the washroom.

MATERIAL SAFETY DATA SHEET

**Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

Color:	White
Odor:	Paint
Physical State:	Liquid
PH:	Not available
Freezing Point:	Not available
Boiling Point:	Not available
Flash Point:	Not applicable
Evaporation Rate:	Slower than ether
Upper Flammability Limit:	Not available
Lower Flammability Limit:	Not available
Vapor Density:	Greater than air
Specific Gravity:	1.32
Solubility (H <sub>2</sub> O):	Not available
Auto Ignition Temperature	Not available
Decomposition Temperature:	Not available
Weight per gallon:	11.02 (Theoretically)
Percent Volatile, wt %:	48.80 (Theoretically)
Percent Volatile, volume %:	64.22 (Theoretically)
Volatile Organic Compound (VOC) Content:	1.5466 lbs/gal
Viscosity:	Not available

<u>Component</u>	<u>Vapor Pressure (mm Hg @ 20°C)</u>	<u>LEL (@ 25°C)</u>
Titanium Dioxide	N/A	N/A
Kaolin	N/A	N/A
Ethylene Glycol	0.08	3.20
Propylene Glycol	0.22	N/A

(N/A = Not applicable)

**Section 10: STABILITY AND REACTIVITY**

Stability:

Stable

Conditions to Avoid:

None known.

Incompatible Materials:

Oxidizing agents and strong acids. Avoid alkalis at high temperature.

Hazardous Decomposition Products:

Combustion products include carbon dioxide, carbon monoxide, and unidentified organic compounds.

Hazardous Polymerization:

Will not occur.

MATERIAL SAFETY DATA SHEET

**Section 11: TOXICOLOGICAL INFORMATION**

Acute Effects:

- Eye: May cause moderate eye irritation including pain, tearing, redness, and swelling.
- Skin: May cause moderate skin irritation including redness, swelling, and rash. Prolonged contact may cause skin damage, defatting, and dermatitis. Absorption through the skin may cause symptoms of exposure as described for inhalation and ingestion.
- Ingestion: Expected to be moderately toxic. May cause gastrointestinal irritation, including sore throat, abdominal pain, nausea, vomiting, and diarrhea. Ingestion may cause central nervous system depression. May cause kidney damage, lumbar pain, oliguria, or uremia. Extreme cases of intoxication may cause unconsciousness and death.
- Inhalation: May cause irritation to the nose, throat, respiratory tract, and other mucous membranes. Symptoms of respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath, and reduced lung function. Exposure to high concentrations of vapor may cause central nervous system depression. Symptoms of central nervous system depression include headache, dizziness, and nausea. Intentional misuse by deliberate concentration and inhalation of this material may be harmful or fatal.

Chronic Effects:

Prolonged occupational overexposure to solvents has been associated with permanent brain and nervous system damage. Chronic overexposure may cause loss of memory, loss of intellectual ability, and loss of coordination. Chronic overexposure may cause lung damage.

Reproductive/Developmental Effects:

Due to the presence of ethylene glycol, this material is presumed to be a teratogen.

Carcinogenicity:

This product contains no carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

**Section 12: ECOLOGICAL INFORMATION**

No data available.

**Section 13: DISPOSAL CONSIDERATIONS**

Dispose of in accordance with federal, state, and local regulations.

**Section 14: TRANSPORT INFORMATION**

US Department of Transportation Classification:

Not regulated.

MATERIAL SAFETY DATA SHEET

**Section 15: REGULATORY INFORMATION**

SARA 313 Information:

<u>Component</u>	<u>CAS#</u>	<u>% by Wt.</u>
Ethylene Glycol	107-21-1	1-5

**Section 16: OTHER INFORMATION**

NFPA 704: National Fire Protection Association

Health = 1      Flammability = 0      Reactivity = 0

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard

Disclaimer:

This information has been compiled from sources considered to be dependable and is accurate to the best of Central Petroleum Company's knowledge; however, the Central Petroleum Company makes no warranty whatsoever, expressed or implied, of merchantability or fitness for particular purpose regarding the accuracy of such data or the results to be obtained from the use thereof. The Central Petroleum Company assumes no responsibility for injury to recipient or third persons or for any damage to any property and recipient assumes all such risks.