

Cen-Pe-Co Hydrostatic Fluid

Safety Data Sheet

SECTION 1: PRODUCT AND COMPANY INFORMATION

 Manufacturer
 Central Petroleum Company, 201 East Lincoln St., Walcott, IA 52773-0116

 Telephone
 563-284-6221 (M-F: 8:00-3:00 CT)
 Fax
 563-284-5124

Product Name(s) Cen-Pe-Co Hydrostatic Fluid

Common Name Lubricating Oil

Use Lubricating Oil CAS Number Mixture

Emergency Contact / Number CHEMTREC 1-800-424-9300

SECTION 2: HAZARD IDENTIFICATION

Hazards Not Classified
Signal Word Not Applicable
Precautionary Statements Not Applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component NameCAS#Component%Highly refined base oil64742-65-0, 64742-56-9>90Performance additivesMixture5 – 10

SECTION 4: FIRST AID MEASURES

Skin Contact

Wash exposed areas promptly with water and mild soap. Remove contaminated clothing immediately and launder before reuse. Seek medical attention if irritation occurs and persists.

Eye Contact

Flush with water for 15 minutes. Seek medical attention if irritation occurs and persists.

Inhalation

Remove victim to fresh air. Seek immediate medical attention if symptoms persist.

Ingestion

Rinse mouth if victim is conscious but do not induce vomiting. Contact a physician or poison control center immediately for guidance.

Most Important Symptoms / Effects

May cause reversible skin, eye and respiratory irritation. Ingestion is not expected to be more than slightly toxic but may cause gastrointestinal irritation. See Section 11 for further information.

Indication of Immediate Medical Attention and Special Treatment, If Necessary

Persistent eye or skin irritation, ingestion, gastrointestinal or respiratory distress. See Section 11.

SECTION 5: FIREFIGHTING MEASURES

Suitable Extinguishing Media

Water fog, foam, CO₂, dry chemical. Water stream may splatter burning oil. Use a water spray to cool fire-exposed containers, structures and to protect personnel.

Special Firefighting Procedures

Clear fire area of unprotected and untrained personnel. Do not enter confined fire space without full equipment and a positive pressure NIOSH approved self-contained breathing apparatus.

Unusual Firefighting Hazards

Combustion consumes oxygen and produces carbon dioxide, carbon monoxide and other, possibly toxic gases.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions

Isolate release area and keep unnecessary or untrained people away. Floor and surfaces may be slippery. See Section 8 for personal protection gear.

Environmental Precautions

Contain spill if it can be done with minimal risk. Prevent liquid from entering drains, sewers or waterways. Advise EPA, state or local agencies as required.

Methods for Cleaning Up

Dike area and absorb spill with sand or other inert material. <u>Using sawdust or other combustible absorbent will create a more combustible solid.</u> Vacuum or sweep up large spills and place in a disposal container. Dispose of properly.

SECTION 7: HANDLING AND STORAGE

Handling

Keep containers closed when not in use. Keep away from heat, open flames, and strong oxidizing agents. See Section 8 for personal protection gear. Do not pressurize, cut, drill, grind, weld or perform similar operations on or near containers.

Storage

Store materials in closed, labeled containers at ambient temperature. Avoid sources of ignition and excessive heat. Empty containers may contain flammable residue or vapors.

SECTION 8: EXPOSURE CONTROL AND PERSONAL PROTECTION

Exposure Limits

Component Name	OSHA PEL	ACGIH TLV
Petroleum oil (mist)	5 mg/m3	5 mg/m3

Engineering Controls

Use appropriate ventilation to maintain airborne concentration limits below exposure limits.

Eve and Face Protection

Wear safety glasses with side shields or goggles; use face shield if splashing is possible.

Skin Protection

Wear oil or chemical resistant gloves such as nitrile; wear other protective clothing as appropriate the work assignment.

Respiratory Protection

Use a properly fitted NIOSH respirator in areas where the exposure is unknown or above the OSHA PEL or ACGIH TLV,

General Hygiene

Follow accepted work practices for handling a combustible material. Do not ingest. Avoid breathing vapors or mists. Use good hygiene practices when handling product, including changing and laundering work clothes after use. Avoid prolonged or repeated contact with skin, eyes and clothing. Do not eat, drink or smoke in areas where this chemical is used or stored. Wash thoroughly with soap and water after task or shift, when using the restroom or before eating.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State	Red liquid	Flash Point	>320 °F
Specific Gravity (Water=1)	0.89 - 0.92	Upper Flammability Limits	Not Determined
Evaporation Point	Not Determined	Lower Flammability Limits	Not Determined
рН	Not Applicable	Auto-ignition Temperature	Not Determined
Solubility in Water	Negligible	Decomposition Temperature	Not Determined
Odor	Petroleum	Vapor Pressure	Not Determined
Odor Threshold	Not Determined	Vapor Density (Air-=1)	>1
Melting/Freezing Point	Not Determined	Partition Coefficient	Not Determined
Boiling Range	Not Determined	Viscosity	>20.5 cSt @100 °F
Initial Boiling Point	Not Determined	Critical Temperature	Not Determined

Note: Physical and chemical properties are provided for safety, health and environmental considerations and do not fully represent product specifications. Those should be requested separately.

SECTION 10: STABILITY AND REACTIVITY

Stability

Stable under normal conditions of storage and handling.

Conditions to Avoid

Sparks, fire, and extreme temperatures. Acids and oxidizing agents.

Hazardous Decomposition / Byproducts

Smoke, fumes, CO, CO₂, and other, possibly toxic, organic compounds may form or be released in a fire or at high temperature.

Hazardous Polymerization

Will not occur.

Polymerization Conditions to Avoid

Not Applicable

SECTION 11: TOXICOLOGICAL INFORMATION

Specific toxicity tests have not been conducted on this mixture. In accordance with OSHA's Hazard Communication Standard 1910.1200, this mixture is assumed to have the same health hazards as its significant components.

Likely Routes of Exposure

Eyes, skin, inhalation

Inhalation

Vapors from product at high temperature may cause upper respiratory tract irritation.

Eye Contact

Product or product vapors not expected to be irritating or may cause slight irritation.

Skin Contact

May cause slight irritation. Prolonged or repeated contact may cause dermatitis. Symptoms include redness, edema, drying, and cracking.

Ingestion

Not expected to be more than slightly toxic.

Carcinogenicity

This product contains severely refined mineral oils. No components of this product are found to be carcinogens by NTP, IARC or OSHA. Prolonged or repeated contact with used oils may cause skin cancer.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity Not Determined Mobility Not Determined Degradability Not Determined Bioaccumulation Not Determined

SECTION 13: DISPOSAL CONSIDERATION

Dispose of this product in compliance with all applicable federal, state and local regulations.

SECTION 14: TRANSPORT INFORMATION

Proper Shipping Name Not Regulated

SECTION 15: REGULATORY INFORMATION

TSCA Status

All components are listed in the TSCA inventory

SARA 311/312 Reporting Categories

None

SARA 313 Reportable Ingredients

None

SECTION 16: OTHER INFORMATION

NFPA Rating 1-1-0

0=minimal hazard, 1=slight hazard, 2=moderate hazard, 3=severe hazard, 4=extreme hazard

Department Issuing SDS Health and Safety

Disclaimer

This information has been compiled from sources considered to be dependable and is accurate to the best of Central Petroleum Company's knowledge; however, the Central Petroleum Company makes no warranty whatsoever, expressed or implied, of merchantability or fitness for particular purpose regarding the accuracy of such data or the results to be obtained from the use thereof. The Central Petroleum Company assumes no responsibility for injury to recipient or third persons or for any damage to any property and recipient assumes all such risks.