

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 11/02/2014

1 Identification

- **Product identifier:** *Cen-Pe-Co Moly H-D Pressure Lube*
- **Trade name:** *Cen-Pe-Co Moly H-D Pressure Lube*
- **Recommended use:** *Lubricating grease*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*Central Petroleum Company
 201 East Lincoln Street
 Walcott, IA 52773-0116*
- Telephone Number: (563) 284-6221*
- **Emergency telephone number:** *CHEMTREC 800-424-9300*

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

Eye Irrit. 2B H320 Causes eye irritation.

- **Label elements**
- **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*
- **Hazard pictograms**



GHS07

- **Signal word** *Warning*
- **Hazard-determining components of labeling:**
Asphaltic Resin
- **Hazard statements**
*Causes skin and eye irritation.
 May cause respiratory irritation.*
- **Precautionary statements**
*If medical advice is needed, have product container or label at hand.
 Keep out of reach of children.
 Read label before use.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Wear protective gloves.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Specific treatment (see on this label).
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 Call a poison center/doctor if you feel unwell.*

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 11/02/2014

Trade name: Cen-Pe-Co Moly H-D Pressure Lube

(Contd. of page 1)

If skin irritation occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 If on skin: Wash with plenty of water.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Store in a well-ventilated place. Keep container tightly closed.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

	Asphaltic Resin	20-<25%
1317-33-5	molybdenum disulphide	1-<2.5%

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

· **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 11/02/2014

Trade name: Cen-Pe-Co Moly H-D Pressure Lube

(Contd. of page 2)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
 - Do not allow product to reach sewage system or any water course.
 - Inform respective authorities in case of seepage into water course or sewage system.
 - Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic (50-100%)

ACGIH TLV Long-term value: 5 mg/m³

OSHA PEL Long-term value: 5 mg/m³

Asphaltic Resin (20-<25%)

REL Ceiling limit value: 5* mg/m³
*15-min; See Pocket Guide App. A

TLV Short-term value: 10 mg/m³
Long-term value: 5 mg/m³
*inh. fraction; as benzene-soluble aerosol; BEIp

64742-52-5 Distillates (petroleum), hydrotreated heavy naphthenic (2.5-<10%)

ACGIH TLV Short-term value: 10 mg/m³

Long-term value: 5 mg/m³

OSHA PEL Long-term value: 5 mg/m³

(Contd. on page 4)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 11/02/2014

Trade name: Cen-Pe-Co Moly H-D Pressure Lube

(Contd. of page 3)

7782-42-5 Graphite (1- <2.5%)

PEL	Long-term value: 15 mppcf* mg/m ³ *impinger samples counted by light field techn.
REL	Long-term value: 2.5* mg/m ³ *respirable dust
TLV	Long-term value: 2* mg/m ³ all forms except graphite fibers; *resp. fraction

1317-33-5 molybdenum disulphide (1- <2.5%)

PEL	Long-term value: 15* mg/m ³ *Total dust
TLV	Long-term value: 10* 3** mg/m ³ as Mo; *inhalable fraction ** respirable fraction

· **Ingredients with biological limit values:**

Asphaltic Resin (20- <25%)

BEI	- Medium: urine Time: end of shift at end of workweek Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 11/02/2014

Trade name: *Cen-Pe-Co Moly H-D Pressure Lube*

(Contd. of page 4)

· **Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form:	Semi-Solid
Color:	Light grey
Odor:	Petroleum-like
Odour threshold:	Not determined.

· **pH-value:** Not applicable.· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	370 °C (698 °F)

· **Flash point:** 255 °C (491 °F)· **Flammability (solid, gaseous):** Not determined.· **Ignition temperature:** > 315 °C (> 599 °F)· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** Product does not present an explosion hazard.· **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

· **Vapor pressure:** Not applicable.· **Density at 20 °C (68 °F):** 0.95422 g/cm³ (7.963 lbs/gal)· **Relative density** Not determined.· **Vapour density** Not applicable.· **Evaporation rate** Not applicable.· **Solubility in / Miscibility with**

Water:	Insoluble.
---------------	------------

· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**

Dynamic:	Not applicable.
Kinematic:	Not applicable.

· **Solvent content:**

Organic solvents:	0.0 %
--------------------------	-------

Solids content:	7.9 %
------------------------	-------

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 11/02/2014

Trade name: Cen-Pe-Co Moly H-D Pressure Lube

(Contd. of page 5)

· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	29070 mg/kg (rat)
Dermal	LD50	8457 mg/kg (rabbit)
Inhalative	LC50/4 h	137 mg/l

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

Asphaltic Resin

2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 11/02/2014

Trade name: Cen-Pe-Co Moly H-D Pressure Lube

(Contd. of page 6)

- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, ADN, IMDG, IATA	not regulated
· UN proper shipping name	
· DOT, ADN, IMDG, IATA	not regulated
· Transport hazard class(es)	
· DOT, ADN, IMDG, IATA	
· Class	not regulated
· Packing group	
· DOT, IMDG, IATA	not regulated
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	-

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· Section 355 (extremely hazardous substances):
None of the ingredients is listed.
· Section 313 (Specific toxic chemical listings):
None of the ingredients is listed.
· TSCA (Toxic Substances Control Act):
All ingredients are listed.

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 11/02/2014

Trade name: Cen-Pe-Co Moly H-D Pressure Lube

(Contd. of page 7)

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

Asphaltic Resin

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

Asphaltic Resin

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07

· **Signal word** Warning

· **Hazard-determining components of labeling:**

Asphaltic Resin

· **Hazard statements**

Causes skin and eye irritation.

May cause respiratory irritation.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 11/02/2014

Trade name: Cen-Pe-Co Moly H-D Pressure Lube

(Contd. of page 8)

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information has been compiled from sources considered to be dependable and is accurate to the best of our knowledge; however, Central Petroleum Company makes no warranty whatsoever, expressed or implied, of merchantability or fitness for particular purpose regarding the accuracy of such data or the results to be obtained from thereof. Central Petroleum Company assumes no responsibility for injury to recipient or third persons or for any damage to any property and recipient assumes all such risks.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

USA